

RECEIVED
CENTRAL FAX CENTER

OCT 19 2009

In the Claims:

1. (Cancelled) without prejudice.
2. (Currently amended) A method for producing wash-free rice which does not require washing before cooking in a waterless environment, comprising steps of:
 - performing a wash-free rice producing operation including:
 - preparing polished rice from brown rice polished by a built-in rice polishing machine and sifted by a built-in sifting machine and/or polished rice from outside sources;
 - preparing parched bran used as an abrasive for polishing rice;
 - preparing a mixture consisting of said polished rice and said abrasive in a desired ratio;
 - stirring said mixture in a tank by revolving stirring blades such that said polished rice and said abrasive are mutually rubbed in order to strip sticking bran including skin bran and foreign debris from the surfaces of rice grains;
 - sifting said stirred mixture in order to separate bran from the rice grains;
 - separating residual sticking bran and foreign debris from the sifted rice grains in order to obtain finished wash-free rice;
 - recovering the separated bran for recycling the bran as the abrasive, wherein:
 - in said stirring step, a revolving rate of said stirring blades is raised, if a surface level of said mixture in said tank is lower than a predetermined level either (1) at the end of the wash-free rice producing operation or (2) said mixture is not filled to capacity of said tank;
 - ~~wherein supplying~~ ionized air from an ion generating apparatus ~~is supplied~~ to said sifting step and said separating step in order to eliminate static electricity so that ~~the~~ foreign debris ~~such as fine powders and the like~~ are prevented from sticking to the finished rice grains again; and
 - wherein in said separating step, said ionized air flows upward, while rice grains flow downward to eliminate static electricity ~~more~~ effectively from the rice grains.
3. (Currently amended) The method according to claim 2, wherein:

said sifting step is carried out in a tilted cylindrical sifting machine of which contour is formed by a mesh net such that said bran is separated from rice grains as said mixture is being flowed downward by revolving said tilted cylindrical sifting machine.

4. (Currently amended) The method according to claim 2, wherein:

said separating step is a step for separating foreign debris ~~such as fine powders and the like~~ sticking to the surface of the sifted rice grains, and

said separating step is carried out by one or more finishing units, each of said finishing unit comprising:

a supply guide means for supplying rice grains uniformly;

a cylindrical rotary brushing means for brushing the surfaces of the rice grains;

a regulating means for smoothing a layer of supplied rice grains and regulating a holdup of the supplied rice grains, and

a combing wedge for cleaning brushes of said cylindrical rotary brushing means, wherein:

the rice grains are supplied uniformly in a reverse direction to a revolving direction of said cylindrical rotary brushing means as regulating the holdup and a retention time of the rice grains so that the rice grains are rubbed by said cylindrical rotary brushing means in order to strip foreign debris ~~such as fine powders and the like~~ sticking to the surfaces of the rice grains;

finished rice grains are taken out as wash-free rice; and

the separated foreign debris ~~such as fine powders and the like~~ are sucked and discharged by a solid-gas separating means.

5. (Cancelled) without prejudice.

6. (Cancelled) without prejudice.

7. (Currently amended) An apparatus for producing wash-free rice which does not require washing before cooking, comprising:

a polished rice tank for accommodating polished rice from brown rice polished by a built-in raw rice polishing machine and sifted by a built-in sifting machine or polished rice from outside sources;

a stirring means for mixing a mixture consisting of the polished rice and an abrasive in a desired ratio by revolving stirring blades;

a transportation means for transporting said stirred mixture consisting of polished rice and bran;

a sifting means for sifting bran from the polished rice;

a water-free separating device means comprising cylindrical rotary brushers ~~brushing means~~ for stripping residual foreign debris ~~powders such as fine powders and the like~~ from the surfaces of rice grains in order to obtain finished wash-free rice grains; and

a separated bran recovering means for recycling the bran as the abrasive, wherein:

said stirring means comprises:

a vertical revolving axis equipped in a vertical rotary housing:

a plurality of revolving blades arranged radially around said vertical revolving axis in a plurality of stages;

a shut-off valve arranged at the bottom of said vertical rotary housing;

a control means for controlling a revolving rate of said revolving blades in accordance with a level of the mixture in said vertical rotary housing and for controlling a supply amount of the stirred mixture ~~to the next step~~;

~~a static electricity eliminating means~~ an ionized air apparatus connected to said sifting means and separating device ~~means for eliminating static~~ electricity; and

~~said static electricity eliminating means~~ said ionized air apparatus comprises an ionized air generator ~~generating~~ apparatus and an ionized air transporting means, and wherein:

in said separating device ~~means~~, said ionized air flows upward, while rice grains flow downward for eliminating static electricity ~~more~~ effectively from the rice grains.

8. (Currently amended) The apparatus according to claim 7, wherein:

said sifting means is a tilted cylindrical sifting machine of which contour is formed by a meshed net; and

one or more series of guides made of a plurality of baffle plates are arranged obliquely inside of said tilted cylindrical sifting machine so as to sift the mixture as being revolved and moved downward for separating the bran from the rice grains.

9. (Currently amended) The apparatus according to claim 7, wherein:

said water-free separating means ~~is a means~~ device is for separating foreign debris such ~~as fine powders and the like~~ sticking to the surface of the sifted rice grains, and

said water-free separating means device is constituted by one or more separating units, each of said separating units comprising:

a supply guide means for supplying rice grains uniformly;

a cylindrical rotary brushers ~~brushing means~~ for brushing the surfaces of the rice grains;

a regulating means for smoothing a layer of supplied rice grains and regulating a holdup of the supplied rice grains; and

a combing wedge for cleaning ~~brushes of~~ said cylindrical rotary brushers ~~brushing means~~, wherein:

foreign debris ~~such as fine powders and the like~~ are separated from rice grains; and

said separated foreign debris ~~such as fine powders and the like~~ are sucked and discharged by a solid-gas separating means.

10. (Currently amended) The apparatus according to claim 9, wherein:

said separating unit further comprises:

a downwardly tilted supply guide means constituted by a base plate and parting plates widening toward their end portions arranged on the base plate;

a said cylindrical rotary brushers ~~brushing means arranged comprising plural~~ brushes on its cylindrical body below the end of said supply guide means, wherein[,] the brushes are revolved so as to lift falling rice grains;

a said regulating means for smoothing a layer of the supplied rice grains and for regulating a holdup of the supplied rice grains ~~by varying~~ varies a gap between said cylindrical revolving ~~brushing means as~~ rotary brushers by regulating a tilting angle of said regulating means in accordance with supplied amount of rice grains; and

a combing wedge which ~~always~~ cleans the brushes of said cylindrical rotary brushers ~~brushing means~~.

11. (Currently amended) The apparatus according to claim 9, wherein:

said separating unit comprises:

a supply guide means;

a supply guide aiding means;

a cylindrical rotary brusher ~~brushing means~~; and

a combing wedge; wherein:

said supply guide means and supply guide aiding means[,] ~~is~~ are each constituted by a permeable net with a sifting structure[,] ~~are and~~ arranged at a predetermined slanting angle;

a gap formed between ~~the an~~ end of said supply guide means and ~~the an~~ end of said cylindrical rotary brusher ~~brushing means~~ is maintained such that falling rice grains are lifted by ~~the~~ revolving brushes of said cylindrical rotary brusher ~~brushing means~~; and

said combing wedge ~~always~~ cleans the brushes of ~~said cylindrical revolving brushing means~~; and

~~all components are designed beforehand in order to fit said all components in predetermined position easily.~~

12. (Cancelled) without prejudice.